

EA 34



## *Installation and Operation Manual*



### **ADCS-III** *Analog to Digital Converter and Switcher*

Manual update 08/22/2007

Firmware Version 1.04

Due to the dynamic nature of product design, the information contained in this document is subject to change without notice. Broadcast Tools, Inc., assumes no responsibility for errors and/or omissions contained in this document. Revisions of this information or new editions may be issued to incorporate such changes.

*Broadcast Tools® is a registered trademark of Broadcast Tools, Inc.  
Copyright, 1989 - 2005 by Broadcast Tools, Inc. All rights reserved.  
No part of this document may be reproduced or distributed without permission.*

Visit [www.broadcasttools.com](http://www.broadcasttools.com) for important product update information.

## INTRODUCTION

Thank you for your purchase of the **Broadcast Tools® Analog to Digital Converter and Switcher**, which we will refer to throughout the manual as the **ADCS-III**. We're confident this product will give you many years of dependable service. This manual is intended to give you all the information needed to install and operate the product.

## SAFETY INFORMATION

Only qualified personnel should install Broadcast Tools® products. Incorrect or inappropriate use and/or installation could result in a hazardous condition.

Broadcast Tools, Inc., is unable to support NON-Broadcast Tools software/hardware or NON-Broadcast Tools computer hardware/software problems. If you experience these problems, please research your hardware/software instruction manuals or contact the manufacturers technical support department.

## WHO TO CONTACT FOR HELP

If you have any questions regarding your product or you need assistance, please contact your distributor from whom you purchased this equipment.

If you would like more information about Broadcast Tools® products, you may reach us at:

### **Broadcast Tools, Inc.**

131 State Street  
Sedro-Woolley, WA 98284-1540 USA  
Voice: 360.854.9559  
Fax: 866.783.1742

Internet Home Page: [www.broadcasttools.com](http://www.broadcasttools.com)  
E-mail: [support@broadcasttools.com](mailto:support@broadcasttools.com)

**THANK YOU FOR CHOOSING  
BROADCAST TOOLS® BRAND PRODUCTS!**

Broadcast Tools is a Veteran Owned Business



Designed, Assembled and Supported in WA State, USA




**Broadcast Tools®** Products, as with any electronic device, can fail without warning. Do not use this product in applications where a life threatening condition could result due to failure.



This manual should be read thoroughly before installation and operation.

### WEBSITE:

Visit our web site for product updates and additional information.




## Product Description

The ADCS III provides professional quality 24-bit A/D conversion, along with AES path insertion and interruption functions. The ADCS III may be configured as a standalone A/D converter or to switch AES or stereo analog inputs into another AES stream. The ADCS III is a perfect companion for analog EAS encoders/decoders to be inserted into an AES program stream. The ADCS III is equipped with relay bypass in case power is removed from the unit. The A/D converter may be configured for sample rates of 44.1 or 48kHz (32kHz may be special ordered) or an external word clock from 32 to 96kHz. Additional features include; balanced stereo analog input, AES input, AES output and remote control via plug-in euroblock connectors. The front panel is equipped with left and right analog input trimmers, overload, audio presence and power LED indicators. Input transfer switches are provided along with LED indicators. Most front panel functions and status are available on the rear panel connector. The ADCS III is powered by a surge protected internal bipolar 15 vdc power supply affording superior headroom and high definition audio. The ADCS III may be set on a desktop, mounted on a wall or up to three units may be mounted on the optional RA-1, Rack-Able mounting shelf.

### WEBSITE:

*Visit our web site for product updates and additional information.*



### DESCRIPTION

## Installation

Please examine your ADCS-III carefully for any damage that may have been sustained during shipping. If any is noted, please notify the shipper immediately and retain the packaging for inspection by the shipper. The package contains the ADCS-III, 16 VAC @ 600 ma wall power transformer and this manual.

Installation of the ADCS-III in **high RF environments** should be performed with care. Shielded cable is suggested for all audio connections. All shields should be tied to the “G” Ground terminals. The station ground should be connected to the chassis ground screw located on the far right side of the ADCS-III as viewed from the rear. It is recommended that all cables connected to the ADCS-III be looped through ferrite cores to suppress RF. Surge protection with RF filtering such as the Tripp-Lite “ISOBAR 4 or 6” is also suggested for the wall transformer.

**To gain access to the ADCS-III components, remove power and the top cover allen screw. When the configuration is completed, reinstall the cover, screw and power.**

**L/R Analog Inputs** Hi Z, active balanced. Connect your source equipment to the left/right input - and + terminals on the plug-in euroblock connector. For monaural sources, tie the left and right inputs together. Be sure to observe correct phasing. NOTE: If the source feeding the ADCS III is unbalanced, install a jumper between Lt- or Rt- terminal and GND.

**AES Input 1** Connect your main AES source equipment to this plug-in euroblock connector. When used as an EAS insert switcher, this would normally be the feed from your source equipment.

**AES Output** Connect this plug-in euroblock connector to the AES input on your processing equipment.

**Word clock input** Balanced word clock input. Accepts all standard digital audio sample rates from 32 to 96kHz. SW3-2 & SW3-3 must be configured to activate this input.


**Remote Control** The plug-in euroblock connector provides access to the front panel input selection switches and a SPDT input tally relay. Applying a closure across terminals 1A & 1B will select AES input 1. Applying a closure across terminals 2A & 2B will select the analog input. JP1 is used to configure AES input 1 opto-isolator for either wet or dry operation. The factory setting is DRY, which accepts dry contact closures, open

collectors, etc. In this configuration, 1A is ground and 1B is the cathode of the opto-led. To configure for wet operation (5 to 24vdc), move the jumper on JP1 to pins 2 & 3. JP2 is used to configure the analog inputs opto-isolator for either wet or dry operation. The factory setting is DRY, which accepts dry contact closures, open collectors, etc. In this configuration, 2A is ground and 2B is the cathode of the opto-led. To configure for wet operation (5 to 24vdc), move the jumper on JP2 to pins 2 & 3.

Remote input tally is available from the SPDT relay. The terminals are labeled N.O., CM and N.C. When AES Input 1 is selected, there will be continuity between the N.C. and CM contacts.

### WEBSITE:

*Visit our web site for product updates and additional information.*



## INSTALLATION

## Programming

### “Setup” DIPSwitch settings.

**Note:** When changing SW3, be sure to press the front panel recessed “reset” switch.

<b>SW3-1</b>	<b>OFF:</b>	44.1 kHz sample rate (factory default).
	<b>ON:</b>	48 kHz sample rate. May be special ordered for 32 kHz.
<b>SW3-2</b>	<b>OFF:</b>	External Clock
	<b>ON:</b>	Internal ( <b>factory default</b> ).
<b>SW3-3</b>	<b>OFF:</b>	External clock, 30 to 59kHz (factory default).
	<b>ON:</b>	External clock, 59 to 96kHz.
<b>SW3-4</b>		Feature creep

### “Options” logic operation DIPSwitch. SW4 sets the mode of operation in binary format.

**NOTE:** All switches (and/or opto’s) have a 50ms debounce.

**Mode 0:** Flip Flop mode 0 (**Last source selected**). The unit will power-up for the first time with AES Input one (default) selected. To select the analog input two, press the front panel input two push button and/or activate the remote control terminals. To select AES Input one, press the front panel input one push button and/or activate the remote control terminals. The non-volatile memory will store the state of the currently selected source and will return to this state after a power outage (referred to as “Last Source Selected”).

**Mode 1:** Flip Flop mode one (**User selected source**). The unit will power-up for the first time with AES Input one selected. To select analog Input two, press the front panel input two push button and/or activate the remote control terminals. To select AES Input one, press the front panel input one push button and/or activate the remote control terminals. The non-volatile memory will store the present state when the desired front panel input switch is held for 3 seconds. The front panel input indicator led’s should flash twice indicating that the command is accepted. During a power outage it will always return to this input.

**Mode 2:** Momentary/Sustained mode. **This is the preferred mode for EAS insertion control.**

**Operation prior to 11-29-2006:** In this mode, the unit will always power-up with AES Input one selected. The front panel input selection push buttons and remote control terminals 2A and 2B are disabled. When remote control terminals 1A and 1B are closed, the analog input (two) is activated. When the closure is removed, AES input one is selected.

**Operation after 11-29-2006:** The unit will power-up for the first time with AES Input one selected. To select the analog input two, press the




front panel input two push button. To select AES Input one, press the front panel input one push button. The non-volatile memory will store the state of the currently selected source and will return to this state after a power outage (referred to as “Last Source Selected”). When remote control terminals 1A and 1B are closed, analog input (two) is activated. When the closure is removed, the state of the last selected source prior to the remote input 1A and 1B being activated will be selected.

**NOTE:** When remote control terminals 1A and 1B are not active (closed), the front panel input push button switches are active.

**Mode 3:** Feature creep.

## WEBSITE:

*Visit our web site for product updates and additional information.*



## Operation

### Power

Insert the power plug into the power jack on the ADCS-III and the wall transformer into the proper AC outlet. Verify that the power LED is lit.

### Act

The **ACT**ivity LED is set to trip at levels above  $-5\text{dBu}$ .

### Clip


This led is set to illuminate when the input level is at  $+20\text{dBu}$ . The clip led should occasionally flash with normal program activity.

### LT Lvl / RT Lvl

Adjust these controls to the desired AES output level.

## WEBSITE:

*Visit our web site for product updates and additional information.*






## Specifications

Analog Input Level	0dBu to +24dBu. +4dBu analog input provides -20dBfs AES output when adjusted with the front panel trimmers.
Analog Input Impedance	10K $\Omega$ balanced.
Frequency Response	10 to 20kHz +/- 0.5dB.
Distortion	<.001%HD / IMD
Noise	<108dB Ref
AES Output Impedance	110 $\Omega$ , balanced (A/D enabled). Passive when AES input 1 is selected.
Word clock input impedance	75 $\Omega$ , balanced
Word clock input level	5 volts
Word clock input range	32 to 96kHz
Opto-Isolated remote inputs	Dry, 5 volt @ 6ma. Wet, 5 to 24vdc.
Tally relay	SPDT, 30Vdc/1 amp.
Connectors	AES, analog Inputs/Outputs and remote control connections: Plug-in euroblock screw terminals Word Clock; BNC
Power Requirement	16 Vac, 600 ma, wall transformer, Supplied. Surge protected power supply.
Size	1/3" rack space, Painted chassis w/ 4 – 6-32 mounting holes.
Weight	2.0 lb.
Options	RA-1, Rack Shelf. 1 RU. / 220 Vac 50-60 Hz CE wall transformer.

### WEBSITE:

*Visit our web site for product updates and additional information.*



## LIMITED WARRANTY

The term “Buyer” as used in this document refers to and includes both (but only) (a) any person or entity who acquires such an item for the purpose of resale to others (i.e., a dealer or distributor of an item), and (b) the first person or entity who acquires such an item for such person’s or entity’s own use.

Broadcast Tools warrants to each Buyer of any item manufactured by Broadcast Tools that the item will be free from defects in materials and workmanship at the time it is shipped by Broadcast Tools if the item is properly installed, used and maintained.

## EXCLUSIVE REMEDIES

If Broadcast Tools is notified, in writing, of a failure of any item manufactured by Broadcast Tools to conform to the foregoing Limited Warranty within one (1) year following the date of the Buyer’s acquisition of the item, and if the item is returned to Broadcast Tools in accordance with Broadcast Tools’ instructions for confirmation by inspection of the defect (which at Broadcast Tools’ election may include, without limitation, a requirement that the Buyer first obtain a Return Authorization number from Broadcast Tools, that the Buyer furnish proof of purchase in the form of an invoice and/or receipt, and that the Buyer prepay all freight charges associated with any return of the item to Broadcast Tools using such freight service as Broadcast Tools reasonably may specify), Broadcast Tools will repair or replace the defective item, or will refund the purchase price paid by the Buyer for the item. Broadcast Tools shall have the exclusive right to choose between these alternative remedies.

## NO OTHER WARRANTIES OR REMEDIES

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, BROADCAST TOOLS AND ITS SUPPLIERS DISCLAIM ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE; AND THE FOREGOING ALTERNATIVE REMEDIES SHALL BE EXCLUSIVE OF ALL OTHER REMEDIES. THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS. YOU MAY HAVE OTHER RIGHTS, WHICH VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

## NO LIABILITY FOR CONSEQUENTIAL DAMAGES

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, NEITHER BROADCAST TOOLS NOR ANY OF ITS SUPPLIERS SHALL HAVE ANY LIABILITY FOR ANY SPECIAL, INCIDENTAL, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES WHATSOEVER (INCLUDING, WITHOUT LIMITATION, ANY DAMAGES FOR LOST PROFITS, BUSINESS INTERRUPTION, LOSS OF DATA OR INFORMATION, COST OF CAPITAL, CLAIMS OF CUSTOMERS, OR ANY OTHER PECUNIARY LOSS) ARISING OUT OF THE USE OF OR THE INABILITY TO USE ANY ITEM SUPPLIED BY BROADCAST TOOLS, EVEN IF BROADCAST TOOLS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES HAVE ANY LIABILITY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY OR PUNITIVE DAMAGES. THIS LIMITATION OF LIABILITY APPLIES WHETHER A CLAIM IS ONE ALLEGING BREACH OF A CONTRACT OR WARRANTY, NEGLIGENCE OR OTHER TORT, FOR THE VIOLATION OF ANY STATUTORY DUTY, THE FAILURE OF ANY LIMITED OR EXCLUSIVE REMEDY TO ACHIEVE ITS ESSENTIAL PURPOSE, OR ANY OTHER CLAIM OF ANY NATURE. BECAUSE SOME STATES AND JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, THIS LIMITATION MAY NOT APPLY TO YOU.

### **Broadcast Tools, Inc.**

131 State Street  
Sedro-Woolley, WA 98284 • USA

360.854.9559 **voice** • 866.783.1742 **fax**  
support@broadcasttools.com **e-mail**  
www.broadcasttools.com **website**