

# NAB Show 2022

## FEATURED PRODUCTS

**NEW**



### Audio Sentinel® +»Web/RJ **List 509.00**

**Web-enabled Dual Channel Stereo Silence Sensor**  
A next-generation web-enabled two channel stereo silence and phase monitor with integrated, transparent, 2x1 switcher. When silent and/or out-of-phase audio is detected, it can automatically switch to the backup input via mechanical latching relays. Features browser-based HTML5 web interface and support for SSL/TLS email (Gmail etc.), SMS-email, and SNMP.

**NEW**



### ACS 4.4 G2 **List \$809.00**

**4x4 Analog Stereo Matrix Switcher**  
Matrix audio switcher with 4 stereo inputs and 4 stereo outputs. Matrix switching allows any/or all inputs to be assigned to any/or all outputs. Control via front panel, contact closures, open collectors, logic and/or the multi-drop RS-232 serial port (USB or Ethernet optional).

**NEW**



### AES Audio Sentinel® 4»Web **List \$1,489.00**


**Web-enabled Four Channel AES/EBU Silence Monitor**  
Monitor four AES/EBU inputs for digital audio silence, stereo out-of-phase conditions, and AES error. When silence, out-of-phase audio, or AES error is detected the unit can be configured to send email alarm messages, SNMP traps, and trigger open collector alarm outputs. Featuring a HTML5 web interface and support for: SSL/TLS email (Gmail, etc.) and SMS-email notification.

**NEW**



### AES Switcher Sentinel® 4 XLR **List \$749.00**

**Web-enabled 4x1 AES/EBU Switcher**  
A web-based, transparent, four input, one output switcher with mechanical latching relays designed to pass AES/EBU digital audio. It features XLR connectors for audio I/O. It has a browser-based HTML5 web interface and supports SSL/TLS email (Gmail, etc.), SMS-email notification, as well as SNMP.



### 2x16 DA/RJ **List \$299.00**

**2x8 or 1x16 RJ45 Analog Distribution Amplifier**  
Eight channels of stereo or 16 channels of mono audio distribution in a compact and easy to use form factor. Inputs accept professional balanced +4 dBu analog audio input (RJ45) or consumer unbalanced -10 dBV (RCA) audio eliminating the need for an additional unbalanced to balanced level converter.



### SS 8.1 MLR Switcher/Router **List \$659.00**

**8x1 RJ 45 Switcher/Router**  
Transparent eight channel stereo switcher/router with mechanical latching relays and RJ45 audio jacks. Control via front panel, contact closures, open collectors, logic and/or the multi-drop RS-232 serial port (USB or Ethernet optional).

Broadcast Tools is a Veteran Owned Business



Designed, Assembled and Supported  
in WA State, USA.

**BROADCAST**  
*tools*  
PROBLEM SOLVED  
[www.broadcasttools.com](http://www.broadcasttools.com)



Contact your Broadcast Tools  
dealer for pricing.  
[www.BroadcastTools.com/](http://www.BroadcastTools.com/)  
dealer-distributors

# NAB Show 2022

## FEATURED PRODUCTS

**NEW**



### Silence Sentinel® RJ Dual Channel Stereo Silence Sensor

The Silence Sentinel RJ is a two-channel analog stereo silence detector and phase monitor with an integrated 2x1 stereo audio switcher, perfect for automatic back-up switching when silence is detected. It features RJ45 audio I/O and pluggable screw terminal block connectors for alarm relay outputs and remote control inputs.

List \$359.00

**NEW**



### 2x6 DA Plus/RJ 2x3 or 1x6 Analog Distribution Amplifier

Three channels of stereo or 6 channels of mono audio distribution in a compact and easy to use form factor. Inputs accept professional balanced +4 dBu analog audio (RJ45) or consumer unbalanced -10 dBV (RCA) audio eliminating the need for an additional unbalanced to balanced level converter.

List \$259.00

**NEW**



### I/O Sentinel® 4 G2 Web-enabled GPIO Interface

A robust, full-featured Ethernet based data acquisition and remote-control device with four optically isolated status (logic) inputs and four programmable relays. The I/O Sentinel® 4 G2's four optically isolated status/logic inputs may be configured for wet or dry (contact closure) status/logic monitoring.

List \$259.00

**NEW**



### Smart Relay 4 G2 Four Channel Smart GPIO Converter

Provides four independent GPIO interfaces in one box, each equipped with two optically isolated inputs (wet or dry) and a 2PDT relay output. Perfect for converting differing logic levels to contact closures. Functions include: sustained, toggle, set-reset (flip-flop), dual alternate action, or failing/rising edge, along with additional boolean logic functions and pulse stretching (delays) from 50ms to 99 hours, 59 minutes, 59.99 seconds.

List \$249.00



### AES Switcher Sentinel® 2+1 Web-enabled AES/EBU Silence Monitor/Switcher

A three channel AES/EBU silence, phase, and AES error monitor combined with an integrated 3x1 AES switcher featuring a browser-based HTML5 web interface. It is designed to monitor two AES sources and one analog to digital (ADC) source. The AES Switcher Sentinel 2+1 can be configured, monitored, and controlled locally and/or remotely over any IP network and supports SNMP as well as secure SMTP (Gmail etc.)

List \$829.00



### AES DA 2x6 AES/EBU Distribution Amplifier

Six XLR output, two-input AES/EBU distribution amplifier is ideal for distributing AES/EBU signals or word clock at sample rates of up to 96kHz. Two selectable transformer isolated inputs use a standard XLR jack for balanced AES/EBU signals and a RCA jack for S/PDIF signals. The selected input is distributed to 6 transformer isolated AES/EBU outputs XLR jacks. An internal AES/EBU activity detector provides local and remote signal monitoring via front panel LED indicators and a SPDT alarm relay.

List \$399.00



Broadcast Tools is a Veteran Owned Business



Designed, Assembled and Supported  
in WA State, USA.

**BROADCAST**  
*tools*  
PROBLEM SOLVED  
[www.broadcasttools.com](http://www.broadcasttools.com)



Contact your Broadcast Tools  
dealer for pricing.  
[www.broadcasttools.com/](http://www.broadcasttools.com/)  
dealer-distributors