Summer 2023 BR FEATURED PRODUCTS





Audio Sentinel® +»Web/RJ Web-enabled Dual Channel Stereo Silence Sensor

A next-generation web-enabled two channel stereo silence and phase monitor with integrated, transparent, 2x1 switcher. When silent and/or out-of-phase audio is detected, it can automatically switch to the backup input via mechanical latching relays. Features browser-based HTML5 web interface and support for SSL/TLS email (Gmail etc.), SMS-email, and SNMP.



AES Audio Sentinel® 4»Web List \$1,489.00 Web-enabled Four Channel AES/EBU Silence Monitor

Monitor four AES/EBU inputs for digital audio silence, stereo out-of-phase conditions, and AES error. When silence, out-of-phase audio, or AES error is detected the unit can be configured to send email alarm messages, SNMP traps, and trigger open collector alarm outputs. Featuring a HTML5 web interface and support for: SSL/TLS email (Gmail, etc.) and SMS-email notification.



Box O' Relays 6

List \$189.00

Six Channel Optically Isolated Relay Module

Perfect for converting GPO outputs from AoIP systems and other devices to dry contact closures. The outputs can be configured for independent operation, or for flip-flop (set/reset) operation in pairs, and are available via pluggable screw terminal block connectors for ease of installation. The outputs are available via pluggable screw terminal block connectors for ease of installation. Use them to control on-air lights, LED indicators, and other externally powered devices. The opto inputs are available via an RJ45 input jack as well as pluggable screw terminal block connectors.



AES DA 1x6

List \$439.00

AES/EBU Distribution Amplifier

A six XLR output, one-input AES/EBU distribution amplifier ideal for distributing AES/EBU signals or wordclock. It features dual (2x) power input jacks to allow for redundant power with an optional second power supply. Signal bypass is built-in with the XLR AES input passively routing to AES output one on loss of power.



AES Switcher Sentinel® 4 XLR List \$749.00

Web-enabled 4x1 AES/EBU Switcher

A web-based, transparent, four input, one output switcher with mechanical latching relays designed to pass AES/EBU digital audio. Features XLR connectors for audio I/O. It has a browser-based HTML5 web interface and supports SSL/TLS email (Gmail, etc.), SMS-email notification, as well as SNMP.



COA-15/RJ

DB-15 to Dual RJ45 Adapter for Axia Livewire GPIO

Using this adapter you can easily interface an Axia Livewire GPIO port with the BOX O' RELAYS 6 via standard Cat5/6 cabling, converting the port's five GPOs to five isolated SPDT dry contact closure outputs on pluggable screw terminal blocks. The COA-15/RJ also breaks out the GPIs to their own RJ45 jack for ease of installation.

Broadcast Tools is a Veteran Owned Business



PROBLEM SOLVED



Contact for Bredericing Const.

Summer 202

List \$399.00









Silence Sentinel® RJ

Dual Channel Stereo Silence Sensor

The Silence Sentinel RJ is a two-channel analog stereo silence detector and phase monitor with an integrated 2x1 stereo audio switcher, perfect for automatic back-up switching when silence is detected. It features RJ45 audio I/O and pluggable screw terminal block connectors for alarm relay outputs and remote control inputs.

2x6 DA Plus/RJ

List \$289.00

2x3 or 1x6 Analog Distribution Amplifier

Three channels of stereo or 6 channels of mono audio distribution in a compact and easy to use form factor. Inputs accept professional balanced +4 dBu analog audio (RJ45) or consumer unbalanced -10 dBV (RCA) audio eliminating the need for an additional unbalanced to balanced level converter.





List \$289.00

DTD-16 + G2



List \$329.00 DTMF Decoder w/ Relay Outputs and USB/Serial

A full-featured DTMF tone/sequence decoder that is user programmable to decode single tones or sequences up to six tones in length which can be assigned to any one of eight SPST normally open relays, eight open collectors and the USB/RS-232 serial ports. Ethernet optional.




I/O Sentinel® 4 G2

A robust, full-featured Ethernet based data acquisition and remote-control device with four optically isolated status (logic) inputs and four programmable relays. The I/O Sentinel® 4 G2's four optically isolated status/logic inputs may be configured for wet or dry (contact closure) status/logic monitoring.







AES Switcher Sentinel® 2+1 List \$909.00

Web-enabled AES/EBU Silence Monitor/Switcher

A three channel, transparent, AES/EBU silence, phase, and AES error monitor combined with an integrated 3×1 AES switcher featuring a browser-based HTML5 web interface. It is designed to monitor two AES sources and one analog to digital (ADC) source. The AES Switcher Sentinel 2+1 can be configured, monitored, and controlled locally and/or remotely over any IP network and supports SNMP as well as secure SMTP (Gmail etc.)

ACS 4,4 G2

List \$889.00

4x4 Analog Stereo Matrix Switcher

Matrix audio switcher with 4 stereo inputs and 4 stereo outputs. Matrix switching allows any/or all inputs to be assigned to any/or all outputs. Control via front panel, contact closures, open collectors, logic and/or the multi-drop RS-232 serial port (USB or Ethernet optional).



BROADCAST PROBLEM SOLVED www.broadcasttools.com



